

vCam-6 HD

INSPECTION SYSTEM

- 1080p HD camera heads
- 1 Terabyte hard drive
- Four-Hour battery life
- One-touch recording and image capture
- Camera exchange program
- Backward compatible⁽¹⁾

Increase productivity and profitability with the feature-rich vCam-6 inspection camera system. Built tough and reliable for everyday use, the versatile vCam-6 is a good fit for plumbers, contractors, home inspectors, building maintenance supervisors, or anyone looking to inspect the interior of a pipe or duct. Create crisp, detailed HD video inspections with audio comments, text descriptions, footage, date, and timestamps to submit to your customers without worry. Putting in a full day's work is easy with the four-hour battery life and charging on-the-go with the provided AC and DC charging leads.

Designed for ease of use and engineered for dependability, vCam inspection products ensure trouble-free operation with little down time. Extend the capabilities of the system with the smaller accessory Type-MX reel for smaller lines, or increase the inspection diameter with the optional adjustable Type-B skid.

WIFI - Powerful 150' / 45m Range

Daylight viewable HD touch-screen LCD

USB Mini data port for LACP software interface

HDMI video/audio out port

Internal microphone and on-screen distance counter

Record to 1 TB hard drive or USB

Camera test port troubleshooting tool

AC/DC operation with Li-ion rechargeable batteries

Full QWERTY keyboard

Stainless-steel construction reels and camera heads

Field serviceable spring, coiled cable and lanyards

512Hz/640Hz/33kHz sonde and traceable pushrod

Self-leveling 34mm HD Camera

Self-leveling 46mm HD Camera



Camera Heads

	D34-HD	D46-HD
Application:	3" to 6"/76mm to 152mm	4" to 8"/101mm to 203mm
Dimensions:	1.3" / 34mm x 2.9" / 73mm	1.8" / 46 mm x 2.7" / 68.8mm
Lighting:	12.87 Lumens	44.02 Lumens
Resolution:	1080p	1080p
Construction:	Stainless steel housing with Sapphire Lens	
Self-leveling:	Yes	Yes
Environmental:	11 Bar	11 Bar
Focus point:	7.8"/20cm	7.8"/20cm
Field of view:	96 degrees	96 degrees

Type-CP Standard Reel

Dimensions:	28" (L) x 19.7" (W) x 35.8" (H) 710 mm (L) x 500 mm (W) x 910 mm (H)
Construction:	Stainless-steel tubular frame with stainless hardware
Weight:	200ft/30m = 57 lbs. (26kg) 300ft/90m = 68 lbs. (31kg) 400ft/120m = 79 lbs. (36kg)
Environmental:	Water resistant to IP54

Control Module

Dimensions:	14.2" (L) x 5.91" (W) x 12.6" (H) 360 mm (L) x 150 mm (W) x 320 mm (H)
Weight:	12Lbs. / 5.49kg
Screen:	9.7" / 24cm Daylight viewable (1024 x 768)
Battery Life:	Four hour runtime (six hour with sonde off)
Environmental:	Water resistant to IP54 (IEC 60529-Light shower w/ lid closed) Shock resistant (IEC 600682-3-1) (lid closed)

(1) The vCam-6 control module is HD (high definition) when used with the new D34-HD and D46-HD camera heads. The vCam-6 control module is backward compatible with the legacy D18-MX, D26-MX, D34-C, D34-M, and D46-CP analog camera heads but will produce SD (standard definition) video and pictures when used with these cameras.

Local Jack Doheny Distributor:

Please visit our website for full product specifications.

Recommended Locators



VM-540 and vLoc3-Cam



vCam Live View -
Record videos and jpegs
to phone or tablet



VMMMap -
Create detailed maps



MyLocator3 -
Fleet management tool
for locators

MyLocator3

Popular Accessories



Mini-Reel and Cameras



Reel Drip Bags



Rotate and Tilt Mounting Table



Camera Guide Skids



Type-B Adjustable Skid with Light

Jack Doheny Company

777 Doheny Dr, Northville, MI 48167, USA

Tel: 888-936-4369

www.dohenycompany.com

