Reelstrong Utility Fleet
CPT14 Pole/Material Trailer

CPT14
CPT14 Extendable Combination Pole Material Trailer

CAPACITIES
16,100 lbs. GVWR @ 15% Tongue Weight
4,750 lbs. Approx. Curb Weight
11,350 lb Approx. Payload
89.25” Wide
21’ / 26’ / 31’ Retracted & Extended Lengths
Designed to handle a 40-55’ poles

AXLES
Tandem 7K Dexter Torsion Axles

WHEELS & TIRES
(4) 16 x 6K / 8 on 6.5 BC w/ Zeroset
(4) ST-235/85R16 LR-E Tires

BRAKES
12.00” x 2.00” Electric w/ Safety Breakaway Kit

POLE SEAT HEIGHT
45”

POLE SECUREMENT
ALL Pole Rests: 5” H Beam
Winch Binders w/ Ratcheting Breaker Bar

CARGO BED
110.75” L X 63.75” W x 15” H

STANDARD TRAILER BODY
6” X 6” X 3/8” (“Square” for Max Equal Lateral and Vertical Strength) Male Extendable Tongue.
8” X 8” X ¼” Wall Female Tongue Tube
7” X 3” X ¼” Wall Frame
7-Position Adjustable Hitch
⅜” X 36” GR70 Yellow Zinc Safety Chains with Hooks
Removable Male Extension Tongue
Standard Cargo Area
12,000 lbs. Static Front Jack w/ Spring Return
Tailgate Chains
Front Removable / Adjustable Pole Seat Mounted on Front Male Tongue
60” Wide 5” H-Beam Pole Seat w/ EZ-Slide Stanchions (Hitch Extension Recommended to prevent Jack-knifing and Clear Most Step Bumpers)
Six (6) D-Rings Front, Center and Rear for Cargo

WIRING

DOT / ICC-- FMVSS / CMVSS Approved LED ULTRA- HIGH VISIBILITY 180 DEGREE BULLET Marker and Clearance Lights
LED Sealed Beam Rubber Mounted Stop, Turn, Tail and Marker Lights
Internal Cat Track Protects Wiring
Removable Rear Access Door to Access Cat Track and Wiring
Breakaway Kit with Absorbed Glass Mat (AGM) Battery
100% Sealed Heat-Shrinked Wiring Connections w/ Full Loom
FULLY PROTECTED 7 or 6 Way Female Plug acts as Junction Box Recessed in FRAME RAIL. No Easily Damaged Plastic Junction Boxes

STANDARD FEATURES

LIFETIME WARRANTY MEGA-ROLLER 6-ROLLER Telescoping Tongue (NO WEAR PADS TO REPLACE))
SELF-SECURING SECURELOCK™ Tongue Lock Roller System (No Loose Pin)
NON-BINDING/FREEZING EZ-SLIDE POLE-CENTERING STANCHIONS
Oil Bath Hubs
Wheel Chock Holders
Diamond Plate Cross Tongue "High Quality T Latched" Toolbox Driver and Passenger Side Access Doors

PAINT/FINISH

Galvanizing w/ Ten (10) Year Structural Warranty
All Structural Tubing Galvanized on the Inside and Out and Will Probably Last a Lifetime

PT-LB Removable Light Bar

All TIG Welded Aluminum w/ Claw-Tooth for Superior Grip
(2) Two Flag Holders
(4) Four 4” Stop / Turn / Tail Rubber Mounted Sealed Beam LED Lights
(3) Three Center ID Marker Lights
(2) Two Side Marker Lights
35’ Power Cable w/ 7-Way Plug
7-Way REMOVABLE, DOUBLE ENDED NON-HARD WIRED Light Plug. Prevents yank-out damage and easier maintenance. 7-Way ILO 4-Way more readily available