



## Elliott G50F Aerial Lift

### EQ # TBD: Specs

#### **Product Description:**

Elliott G50F HiReach

#### **Product Specifications:**

One new Elliott HiReach G50F having a 55' working height. Unit includes base assembly supporting front mounted rotating turret, hydraulically powered continuous rotation mechanism, oil reservoir mounted to truck frame, oil, and manual hydraulic controls mounted turret. Electronic proportional three stick remote controls on platform. Base mounted "A" type hydraulically powered individually main outriggers. Underslung "A" type outriggers for rear stabilization. High strength steel three section hydraulically telescoping boom with one double acting 6" lift cylinder. One cable carrier to boom tip with cover. Hydraulically self-leveling 40" x 60" top mounted work platform with hydraulic platform rotation and remote leveling from platform. Step to access platform from bed (if space allows) Power take off and pump drive, pressure gauge, pump and holding valves on all cylinders. Remote start/shutdown at upper and lower controls, 12-volt emergency pump with switch at upper and lower controls, PTO hour meter, backup alarm, fire extinguisher, and two body harnesses, triangle kit and lanyards. LED lights to include all bed marker lights, stop, tail and turn. Installed on chassis, tested and ready to operate. Unit certified to ANSI A92.2 for Vehicle-Mounted Elevating and Rotating Aerial Devices. Platform capacity 600 lbs.

#### **BED/ BUMPER OPTIONS**

18' Wood Bed With LED Lights (No Grip Deck Coating)  
Standard Rear Bumper  
Tie Down Rails On Both Sides of Bed (wood/steel)

#### **LIFTING OPTIONS**

5,900 lb. Planetary Winch With Anti-Two-Block Switch, Horn, Two Part Hook, Cable Packer, & 150' 3/8" Cable & Retainer Lug  
1,000 lb. Platform Mounted Jib With Hydraulic Winch Mounted in Platform Floor

#### **PLATFORM ACCESSORIES**

110 Volt Line to Platform  
2) Sign Forks On Platform

#### **PTO OPTIONS**

Hot Shift PTO For Automatic Transmission

#### **TOOL BOX - (ALUMINUM)**

36" x 24" x 24" Aluminum Underbody Mounted (Treadplate-No paint)

#### **ADDITIONAL OPTIONS**

Hydraulic Accessory Lines at Rear of Bed With Flow Control (6 gpm)  
Chassis Rating - 25,999 lbs. GVWR Non CDL

#### **PAINT OPTIONS**

HiReach Unit Painted White, Subframe Painted Black, Outriggers Painted Red (STD)

#### **CHASSIS**

2022 Ford F-650, 270 HP 6.7L Ford V8 Turbo Diesel, 50-State Emissions, Ford Torqshift HD 6-speed automatic transmission, 11R22.5 Tires w/ Steel wheels, Hydraulic brakes, 10,000 lb. FA, 19,000 lb. RA, 26,000 lbs. GVWR, 200" WB/126" CA, 50 gallon fuel tank, Air ride driver - fixed two man passenger Power windows/locks  
Color: White.