



## Reelstrong Utility Fleet GR10 Reel Trailer

### **GR10**

GR10 Self-Loading Reel Trailer

### **CAPACITIES**

13,800 lbs. GVWR @ 15% Tongue Weight

2,300 lbs. Approx. Curb Weight

10,000 lbs. Approx. Payload

Reel Diameter: 125" Max

Reel Width: 60" Max

Reel Bar Diameter: 2.50" Solid w/ Centering Collars

Dimensions: 143"L x 102"W

### **AXLES**

12K lbs. Axle

### **WHEELS & TIRES**

(2) 17.5 x 6.75 HC / 8 on 6.5 BC w/ 0.19 Inset

(2) 235/75R17.5 LR-H Tires

### **BRAKES**

12.25" x 5.00" Electric w/ Safety Breakaway Kit

### **STANDARD TRAILER BODY**

Heavy Duty 6" X 4" X ¼" Frame

6-Position Adjustable Hitch

¾" X 36" GR70 Yellow Zinc Safety Chains with Hooks

8,000 lbs. Static Front Jack

### **WIRING**

DOT / ICC Approved LED Lights and Conspicuity Reflective Tape

FMVSS / CMVSS Standard 108 LED Lighting

Sealed Beam Rubber Mounted Stop, Turn, Tail and Marker Lights

100% Sealed Heat-Shrunked Wiring Connections w/ Full Loom

Breakaway Kit with Absorbed Glass Mat (AGM) Battery

### **STANDARD FEATURES**

BLOCK LOCK™ Technology Provides Industry Leading Safety, Ease of Use, Low Maintenance, and Durability.

Auto-locking Swing Out Reel Bar Retainer w/ Secondary Cylinder Lock

Oil Bath Hubs

**PAINT/FINISH**

I.M.P.A.C.T Intense Metal pH Acid Cleaning Technology

Hydrofluoric, Sulfuric, Phosphoric ACID Blend Cleaning Preparation (Re-used sandblasting material can impregnate metals with oil)

Seams Caulked

Rust Preventative 2-Part Epoxy Primer

Standard Color: White

**9-OVS-OB 9" Bronze Overspin Brake- On Bar**