



FEATURES

- Variable GVWR Range
- Variable Payload Range
- Multiple Axle Configurations
- Maximum Reel Capacity of 120" D x 60" W
- Full Length Cargo Bed with 15" H Side Walls
- Fully Mechanical or Hydraulic 12,000 lb Jack
- Fully Mechanical or Hydraulic Stabilizer Jacks at Rear of Trailer
- A-Frame Toolbox Incorporated into Frame
 1/8" Steel Tread Plate Catwalks Mounted on Each Side of Frame
 Catwalks Lined with Anti-Skid Coating
 Reel Bars Rotate in Self-Lubricating Bronze Bearings

GVWR Range	16,400 - 50,000 lbs
Payload Range	12,400 - 45,000 lbs
Axle Manufacturer	Dexter
Axle Size	7,000 - 22,500 lbs
Tires	235 / 80R16, 215 / 75R17.5
Wheels	16" x 6" , 17.5" x 6.75"
Maximum Reel Diamete	r Up to 120"
Maximum Reel Width	Up to 60"
Reel Bar	2 7/8" or 5" OD
Overall Width	101"
Reel Rack Brake Sizes	8", 12",16", or 20"
Rollers	High Strength Plastic
Jack	Fixed 12,000 lb Drop leg
Fenders	1/8" Tread Plate
Overall Length Range	12' - 35' (Depending on Reel Size)
Tool Box	14" H x 13" D x 78" L Contoured to A-fra
Reel Configurations	2RT, 3RT, 4RT

OPTIONS

- 8" 20" Overspin / Tensioning Brakes Upgrade
- Hydraulic Take Up / Retriever Upgrade
- Roller Guide System Upgrade
- Self Contained Hydraulic Power Unit Upgrade
- Galvanized Finish Upgrade

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.



For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrotherstrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.

DOHENYCOMPANY.COM