



FEATURES

- Variable GVWR Range
- Variable Payload Range
- Length Adjustments of 24', 31', and 38'
- Cargo Bed Equipped with Fold Down Tailgate with Retaining Chains
- Tubular Construction
- 6 Position Adjustable Hitch
- Capable of Accommodating Multiple Reel Configurations
- Multiple Axle Capacities with Air Brake Option
- 4" W x 15' Long Pole Straps at Each Bolster
- Multiple Stanchion and Bolster Configurations
- Electric Lines Ran Internally Through the Extendable Tongue
- Tool Box Mounted in Front of Cargo Area: 14" x 24" x 64"

OPTIONS

- Optional Reel Rack Upgrade
- Optional Take Up and Brake Upgrades
- Optional 60" and 89" Bolster Upgrade
- Galvanized Finish Upgrade
- Construction Package Upgrade
- Bolt Bin and Storage Tray Upgrade

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.

SPECIFICATIONS

GVWR Range	14,000 - 23,500 lbs
Payload Range	10,500 - 18,500 lbs
Axle Manufacturer	Dexter
Axle Size	6,000 - 10,000 lbs
Tires	235 / 80R16 , 215 / 75R17.5, 235 / R1717.5
Wheels	16" x 6" , 17.5" x 6.75"
Maximum Reel Diameter	96"
Maximum Reel Width	54"
Reel Bar	2 7/8" DOM
Overall Width	86"
Reel Rack Brake Sizes	8", 12", 16", or 20"
Jack	12,000 lb Drop Leg
Cargo Bed Dimensions	142" L x 64" W x 15" H
Tool Box Dimensions	14" H x 24" D x 64" W
Overall Length Adjustments	24' , 31' , and 38'
Center Bolster width	89"
Front Bolster widths	45" , 60" , and 89"
Hitch	3" Lunette Eye
Bolster Height	48"

CUSTOM OPTIONS



CONSTRUCTION PACKAGE



GALVANIZED FINISH

