



FEATURES

- Variable GVWR Range
- Variable Payload Range
- Length Adjustments of 20', 25', and 30'
- Cargo Bed 104" L x 64" W x 15" H with (4) D-Rings in Each Corner of Cargo Bed
- Tubular Construction
- 6 Position Adjustable Hitch
- Capable of Accommodating up to a 72" x 54" Reel
- Multiple Axle Capacities
- Various Bolster Packages
- 4" W x 15' L Pole Straps

OPTIONS

- Optional Reel Rack Upgrade
- Optional Hydraulic Take Up Upgrade
- 8" - 16" Overspin / Tensioning Brake Upgrade with Heavy Duty Reel Rack Assembly
- Optional 60" and 89" Bolster Upgrade
- Construction Package Upgrade
- Galvanized Finish Upgrade

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.

SPECIFICATIONS

GVWR Range	16,400 - 23,500 lbs
Payload Range	13,000 - 19,500 lbs
Axle Manufacturer	Dexter
Axle Size	7,000 - 10,000 lbs
Tires	235 / 80R16, 215 / 75R17.5, 235 / 75R17.5
Wheels	16" x 6", 17.5" x 6.75"
Maximum Reel Diameter	72"
Maximum Reel Width	54"
Reel Bar	2 7/8" DOM
Overall Width	86"
Reel Rack Brake Sizes	8", 12", 16"
Jack	Fixed 12,000 lb Drop Leg
Cargo Bed Dimensions	108" L x 64" W x 15" H
Tool Box Dimensions	14" H x 24" D x 64" W
Overall Length Adjustments	20', 25', and 30'
Center Bolster Width	89"
Front Bolster Widths	45", 60", and 89"
Hitch	2 1/2" or 3" Lunette Eye

CONSTRUCTION PACKAGE



CONSTRUCTION PACKAGE



GALVANIZED FINISH UPGRADE



For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrothertrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.