



SKYLIFT
Mini-Linesman MH53 BackYard Utility Bucket & Trailer

STANDARD EQUIPMENT

BOOM: VERSALIFT VST52MHI INSULATED TELESCOPING/ARTICULATING AERIAL DEVICE
WORKING HEIGHT: 53'
SIDE REACH: 30'
PLATFORM: END-MOUNTED ROTATING 24" X 30" X 42" BUCKET
PLATFORM CAPACITY: 400 LBS
INSULATED CATEGORY "C" RATING PER ANSI A92.
1,000LB HYDRAULIC DUAL ARM ARTICULATED JIB
4-AXIS CONTROL
TRUGUARD™ 2.0
HYDRAULIC PLATFORM ROTATOR
HYDRAULIC PLATFORM LEVELING
HYDRAULIC TOOL CIRCUIT AT THE PLATFORM
WEIGHT: 12,500 LBS
LENGTH W/ BOOM: 25'
STOWED HEIGHT: 7'4"
WIDTH: 35" TRACKS CLOSED – 50" TRACKS OPEN
GROUND PRESSURE: 6.8 PSI
ENGINE: 25 HP KUBOTA DIESEL - TIER 4 COMPLIANT
OPEN CENTER HYDRAULIC SYSTEM
CONTROLS: FULL PRESSURE
OUTRIGGERS: HYBRID – RADIAL TYPE
OUTRIGGER SAFETY: OUTRIGGER INTERLOCK SYSTEM
OUTRIGGER SPREAD: REAR 18.5' / FRONT 14' / FRONT TO BACK 20.5'

ACCESSORIES

TRANSFORMER CARRIER PLATFORM
EMERGENCY LOWERING
RADIO REMOTE
HIGH/LOW TWO SPEED THROTTLE
ENGINE START/STOP AT BASKET
SET OF 4 PLASTIC 18 X 18 X 1.5" OUTRIGGER PADS

TRAILER

25,900 LB G.V.W.R. (8' W x 25' L) WITH SOLAR BATTERY CHARGER
SPARE TIRE