



VERSALIFT

VERSALIFT is a leading manufacturer of bucket trucks, digger derricks, aerial lifts and other specialty equipment for power generation, transmission and distribution, investor-owned utility, telecommunications, light and sign, and tree care industries. Working with co-ops, municipalities, government agencies and corporations through its global network of facilities and family of dealers, the company employees nearly 800 associates worldwide.

General Specifications	TMD-4060T
Maximum Capacity Capacity at 10ft Radius	29200 lb (13250 kg) 16600 lb (7550 kg)
HORIZONTAL REACH	
Horizontal Reach (B1) Horizontal Reach (B2) Horizontal Reach (B3)	23.9 ft (7.3 m) 37.9 ft (11.6 m) 50.2 ft (15.3 m)
SHEAVE HEIGHT	
Sheave Height (A1) Sheave Height (A2) Sheave Height (A3)	34.2 ft (10.4 m) 48.0 ft (14.6 m) 60.2 ft (18.3 m)
LOAD RADIUS	
Load Radius (R1) Load Radius (R2) Load Radius (R3)	5.2 ft (1.6 m) 7.6 ft (2.3 m) 9.7 ft (3.0 m)
DIG RADIUS	
Dig Radius (S1) Dig Radius (S2)	21.4 ft (6.5 m) 35.4 ft (10.8 m)

OPTIONS:

- Fiberglass Platform
- Liners Available
- Hard-Wired Electric/Hydraulic Lower Controls
- Radio Remote Controls
- Full Pressure Upper Controls with Boom Sequencing
- Various Single Stick Handles
 - Standard VERSALIFT Handle
 - T-Handle
- 5 FT Underslung Jib
- Hydraulic Tool Power Outlets
- Multi-Part Line Components
- Various Types of Outriggers
- Various Augers
- Various Digger Drives
- Left-Hand Riding Seat
- Lower Boom Stow Limit
- Riding Seat Access Ladder

NOTE:

1. Specifications may vary without prior notice
2. Required GVWR can vary significantly with chassis, lift mounting, location, service body, accessories and desired payload.