

T30/36 BWRC TENSIONER / REEL CARRIER FOR DISTRIBUTION CONDUCTOR INSTALLATION



FEATURES

- Smooth control of conductors up to 3,000 lbs. tension
- Hydraulic bronze disc brakes with equal retarding to each bullwheel.
- Open reeve bullwheels for easy conductor installation and removal.
- 36" bullwheel with replaceable urethane lining segments.
- Tail fairlead with 3 rubber lined rollers.
- Tandem axle with leaf spring suspension.
- Reel capacity up to 72" diameter, 54" wide and 7.000 lbs.
- · Quick change reel shaft with straight vertical lift.
- 16" bronze disc reel brake with manual caliper.

DIMENSIONS & WEIGHT

Unit Length	16'-2"
Unit Width	7'-5"
Unit Height	8'-9"
Unit Weight	3,650 lbs. (approx.)

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.



T30/36 BWRC TENSIONER / REEL CARRIER

FOR DISTRIBUTION CONDUCTOR INSTALLATION

T30/36 BWRC TENSIONER SPECIFICATIONS

Performance:	
	3,000 lbs.
Speed	0-4 m.p.h.
Reel Capacity:	
	72 inch
Shaft Diameter	2-5/8 inch
Bullwheel System:	
Bullwheel Diameter	36 inch
Replacement Linking Segments	
Groove Diameter	1.25 inches
Bullwheel Reeving	Open Sided for Easy Conductor Installation and Removal
Braking System	Infinitely Adjustable Braking Control
Tension Monitoring	
Trailer:	
Axles	
Trailer Brakes	Electric
Tires	(4) 8.75 x 16.5 LT
GAWR	10,400 lbs.
GVWR	11,440 lbs.
Tow Hitch	3 inch Pintle Eye with 4 Height Adjustment
Front Jack	Manual Screw Type with Drop Leg
Rear Jacks	2 - Manual Screw Type with Drop Leg
Trailer Lighting	4 Light System

General Features:

3 Roller Tail Fairlead

Quick Change Reel Shaft Removal with Straight Vertical Lift

Unit Sandblasted, Primed and Painted with Two Coats of Enamel Finish Paint

Optional Equipment:

Air / Hydraulic Trailer Brakes

Manual Reel Shaft Rewind

Hydraulic Reel Shaft Rewind

Hydraulic Reel Shaft Tensioning Brake