



**Reelstrong Utility Fleet  
MRST3-96-60 Three Reel Trailer**

**MRST3-96-60**

MRST3-96-60 Three Reel Stringing Trailer

**CAPACITIES**

34,500 lbs. GVWR

7,000 lbs. Approx. Curb Weight

9,000 lbs. Approx. Payload per reel

Reel Diameter: 96" Max each

Reel Width: 60" Max each

Reel Bar Diameter: 2.50" Solid w/ Centering Collars

Dimensions: 370"L x 102"W

**AXLES**

3 X 10K Dexter Triple Sprung Axles w/ Electric Brakes

**WHEELS & TIRES**

(6) 17.5 x 6.75 HC / 8 on 6.5 BC w/ 0.19 Inset

(6) ST-235/75R17.5 LR-H Tires

**BRAKES**

12.25" x 5.008" Electric w/ Safety Breakaway Kit

**STANDARD TRAILER BODY**

Heavy Duty 8" X 3" X 1/4" Frame

6-Position Adjustable Hitch

1/2" X 36" GR70 Yellow Zinc Safety Chains with Hooks

12,000 lbs. Static Front Jack w/ Spring Return

Ground Lug: Copper Alloy Star Washer Bolted to Frame

Fenders: 1/8" Plate

(2) Rear 12,000 lbs. Jacks

**WIRING**

DOT / ICC Approved LED Lights and Conspicuity Reflective Tape

FMVSS / CMVSS Standard 108 LED Lighting

Sealed Beam Rubber Mounted Stop, Turn, Tail and Marker Lights

Breakaway Kit with Absorbed Glass Mat (AGM) Battery

100% Sealed Heat-Shrunked Wiring Connections w/ Full Loom

**STANDARD FEATURES**

POWERLOCK™ Technology Provides Industry Leading Safety, Ease of Use, Low Maintenance and Durability

Oil Bath Hubs

Wheel Chock Holders

**PAINT/FINISH**

Galvanizing w/ Ten (10) Year Structural Warranty

**16-RB-DI 16" BRONZE HEAVY DUTY OVERSPIN BRAKE**

VENTILATED SELF-COOLING Tru-Stop

Drop-In Style

Qty 3 – 1 at each position