



Reelstrong Utility Fleet PL8 Reel Trailer

PL8

PL8 Manual Load Reel Trailer

CAPACITIES

11,050 lbs. GVWR @ 15% Tongue Weight

1,750 lbs. Approx. Curb Weight

8,000 lbs. Approx. Payload

Reel Diameter: 96" Max

Reel Width: 60" Max

Reel Bar Diameter: 2.5"

Dimensions: 125.25"L x 96"W

AXLES

10K lbs. Sprung

WHEELS & TIRES

(2) 17.5 x 6.75 HC / 8 on 6.5 BC w/ 0.19 Inset

(2) ST-215/75R17.5 LR-H Tires

BRAKES

12.25" x 3.38" Electric w/ Safety Breakaway Kit

STANDARD TRAILER BODY

Heavy Duty 5" X 2" X ¼" Frame

6-Position Adjustable Hitch

¾" X 36" GR70 Yellow Zinc Safety Chains with Hooks

8,000 lbs. Static Front Jack

Ground Lug: Copper Alloy Star Washer Bolted to Frame

Fenders: ½" Plate

(2) Rear 8,000 lbs. Static Stabilizer Jacks

WIRING

DOT / ICC Approved LED Lights and Conspicuity Reflective Tape

FMVSS / CMVSS Standard 108 LED Lighting

Sealed Beam Rubber Mounted Stop, Turn, Tail and Marker Lights

Breakaway Kit with Absorbed Glass Mat (AGM) Battery

100% Sealed Heat-Shrunked Wiring Connections w/ Full Loom

STANDARD FEATURES

POWERLOCK™ Technology Provides Industry Leading Safety, Ease of Use, Low Maintenance and Durability

Oil Bath Hubs

Wheel Chock Holders

PAINT/FINISH

Galvanizing w/ Ten (10) Year Structural Warranty

16-RB-DI 16" Bronze Heavy Duty Overspin Brake

VENTILATED SELF-COOLING Tru-Stop

Drop-In Style

16-HE-3/8C 6-Bolt 16" Pintle Hitch Extension

(2) Two 3/8" Safety Chains Extended at 52" Long

Extended Breakaway Cable