



Reelstrong Utility Fleet PT15 Pole Trailer

PT15

PT15 Extendable Pole Trailer

CAPACITIES

17,250 lbs. GVWR @ 15% Tongue Weight
3,850 lbs. Approx. Curb Weight
13,400 lb Approx. Payload
95.50" Wide
20' / 25' / 30' Retracted & Extended Lengths
Designed to handle a 40-55' poles

AXLES

15K Dexter Sprung Axle

WHEELS & TIRES

(4) 17.5 x 6.75 HC / 8 on 275mm BC w/ 5.60 Outset
(4) ST-215/75R17.5 LR-H Tires

BRAKES

12.25" x 5.00" Electric

POLE SECUREMENT

ALL Pole Rests: 5" H Beam
Winch Binders w/ Ratcheting Breaker Bar

CARGO AREA

85.5"L X 43.75"W

STANDARD TRAILER BODY

6" X 6" X 3/8" ("Square" for Max Equal Lateral and Vertical Strength) Male Extendable Tongue.
8" X 8" X 1/4" Wall Female Tongue Tube
7-Position Adjustable Hitch
3/8" X 36" GR70 Yellow Zinc Safety Chains with Hooks
Removable Male Extension Tongue
Standard Cargo Area
12,000 lbs. Static Front Jack w/ Spring Return
Fenders: 1/8" Fabricated Diamond Plate

WIRING

DOT / ICC-- FMVSS / CMVSS Approved LED ULTRA- HIGH VISIBILITY 180 DEGREE BULLET Marker and Clearance Lights
LED Sealed Beam Rubber Mounted Stop, Turn, Tail and Marker Lights
Internal Cat Track Protects Wiring
Removable Rear Access Door to Access Cat Track and Wiring
Breakaway Kit with Absorbed Glass Mat (AGM) Battery
100% Sealed Heat-Shrunked Wiring Connections w/ Full Loom
FULLY PROTECTED 7 or 6 Way Female Plug acts as Junction Box Recessed in FRAME RAIL. No Easily Damaged Plastic Junction Boxes

STANDARD FEATURES

LIFETIME WARRANTY MEGA-ROLLER 6-ROLLER Telescoping Tongue (NO WEAR PADS TO REPLACE))

SELF-SECURING SECURELOCK™ Tongue Lock Roller System (No Loose Pin)

NON-BINDING/FREEZING EZ-SLIDE POLE-CENTERING STANCHIONS

Oil Bath Hubs

Wheel Chock Holders

Adjustable Spring Pads

Slipper Springs

Reinforced Spring Hangers

PAINT/FINISH

Galvanizing w/ Ten (10) Year Structural Warranty

All Structural Tubing Galvanized on the Inside and Out and Will Probably Last a Lifetime

PT-LB Removable Light Bar

All TIG Welded Aluminum w/ Claw-Tooth for Superior Grip

(2) Two Flag Holders

(4) Four 4" Stop / Turn / Tail Rubber Mounted Sealed Beam LED Lights

(3) Three Center ID Marker Lights

(2) Two Side Marker Lights

35' Power Cable w/ 7-Way Plug

7-Way REMOVABLE, DOUBLE ENDED NON-HARD WIRED Light Plug. Prevents yank-out damage and easier maintenance. 7-

Way ILO 4-Way more readily available

16-HE-3/8C 6-Bolt 16" Pintle Hitch Extension

(2) Two 3/8" Safety Chains Extended at 52" Long

Extended Breakaway Cable