



**Brooks Brothers Trailers
PTB 162 - 15KE - Extendable Pole Trailer**

CAPACITY:

35,200# GVWR

29,500# Approx. Load Capacity

AXLES:

Tandem 15,000#

Electric Brakes

(8) 215/75R17.5 Tires

(8) 17.5" x 6.75" Wheels

Mud Flaps

Pair of Wheel Chock holders and Chocks

DIMENSIONS:

Length Adjustments: 30" / 38' / 47"

Cargo Bed: 184" L x 39" W

Overall Width: 94"

Bolster Height: 42"

POLE BOLSTERS:

Front Bolster: 95"W Fixed 5" Double C-Channel with 21" Stanchions on Tongue

A-Frame Bolster: Single Pole Cradle with Nylon Strap and Winch Binder

Center Bolster: 95"W Fixed 5" Double C-Channel Construction with 21" Stanchions

Rear Bolster: 95"W Fixed 5" Double C-Channel Construction with 21" Stanchions

TONGUE & HITCH:

8" x 6" x 1/4" Wall Extendable Tongue with Roller and Replaceable UHMW-PE Wear Pads

6 Position Adjustable Hitch Plate

2-1/2" Lunette Eye, 35,000 lbs. Capacity

3/8" x 36"L Galvanized Safety Chains with Safety Hook and Anchor Shackle

A-FRAME & JACK:

8" Structural C-Channel A-Frame

(2) Linked - Drop Leg Jack, 12,000 lb. Static Load Capacity

Drop Leg Jack on A-Frame For Extending Tongue & Strapping Load

MAIN FRAME:

8" x 4" Tubular Frame

10" x 8" Receiver Tube

8" x 4" Tubular Steel Crossmembers Under Rear Bolster

3" Structural C-Channel Crossmembers

FENDERS:

Fabricated 1/8" Steel Diamond Tread Plate Fender Construction
Reinforced with 3" Structural C-Channel at Front and Rear of Fender

ICC & DOT APPROVED LED LIGHTS:

Sealed Beam Rubber Mounted Stop, Turn, Tail and Marker Lights
S.O. Cable Wiring Loom, Clamped on 16" Centers with Rubber Lined Clamps
Wiring Loom Terminated in Junction Boxes
Connections Soldered & Sealed with Heat Shrink Tubing
All Wiring is Ran Internally Inside Extendable Tongue
36" Pigtail With Electrical Plug Type TBD Terminated at Junction Box
6-Way Aluminum Die Cast Plug (Truck Side) in Rear Butt Tube for Light Bar Hook-Up
Breakaway Kit with Sealed Lead Acid Battery & Trickle Charger

LIGHT BAR:

Includes (2) oval rubber mounted sealed beam lights (stop turn and tail); (3) center ID marker lights and two side marker lights.
Light bar is attached to the pole with an adjustable 1/4" chain and wingnut. Standard electric cable length is 25' with 6-Way
Aluminum Die Cast Connector (longer electric cables are provided for longer capacity pole trailers - Entire Assembly is Galvanized)

FINISH:

3 step Triple Hot Dipped Galvanized Finish
All Attaching parts are Painted before Assembly and Installed with Serviceable Fasteners
Rust Prohibitive Two-Part Epoxy Polyamide Primer
Two-Part Acrylic Polyurethane Topcoats
2" Red/White Reflective Tape