



**SKYLIFT
Patriot 50**

STANDARD EQUIPMENT

SKYLIFT 50' DIGGER DERRICK
6,000 LB LIFTING CAPACITY
51 FT SHEAVE HEIGHT
46 kV CATEGORY C BOOM INSULATION
PLANETARY WINCH
12v SOCKET OUTLET
HYDRAULIC OVERLOAD PROTECTION
25' HYDRAULIC HOSE REEL FOR TOOLS AT GROUND
CONTINUOUS BOOM ROTATION
TWO SPEED THROTTLE
FULL PRESSURE CONTROLS AT RIDING COMMAND CONSOLE
25/8" KELLY BAR EXTENSION
18" BULLET TOOTH AUGER
AUGER DRIVE 2 SPEED, 5,800/10,500 FT LBS OF TORQUE
OUTRIGGER PAD CARRIER
AUDIBLE ALARMS ON OUTRIGGERS
AUDIBLE ANGLE ALARMS (FRONT TO BACK & SIDE TO SIDE)
LED WORK LIGHT ON OPERATOR PLATFORM

ACCESSORIES

HYDRAULIC POLE GUIDE (MANUAL TILT)
SINGLE MAN BUCKET - 350 LB. CAPACITY
EMERGENCY LOWERING (DC PUMP)
RADIO REMOTE CONTROLS BELT PACK (INCLUDES START/STOP)
750 LB. CAN HANDLER WITH SHORT JIB
HYDRAULIC BLADE
HYDRAULIC RECOVERY WINCH
BOOM OVER-STOW SWITCH
SET OF (4) PLASTIC 18 X 18 X 1.5" OUTRIGGER PADS
SINGLE SIDED POLE CARRIERS (2)

MOROOKA MST-660-VD CRAWLER CARRIER

ROPS CANOPY
OPEN CANOPY
ENGINE: 76 HP DIESEL TIER 4
SPEED: 7.5 MPH
WIDTH: 77"
GROUND PRESSURE: 5 PSI
ENCLOSED CAB OPTION WITH HEAT & A/C AVAILABLE

TRAILER

25,900 LB G.V.W.R. (8' W X 23' L) (Tri-Axle) W/ SOLAR BATTERY CHARGER