



We are pleased to quote the VERSALIFT SST-40-EIH-02, insulated 40 ft. articulating, telescopic aerial platform lift, 45 ft. working height including the following items:

STANDARD FEATURES

Standard platform capacity of 350 lbs. (158.7 kg).

VERSALIFT TruGuard™ dielectric isolating system with right hand single stick control. All control handles are isolated and tested per ANSI 92.2. The high resistive dielectric system is protected from direct environmental and job related contamination.

TruGuard™ technology incorporates the use of full hydraulic controls with durable metal handles and linkages.

180° hydraulic platform rotator.

Full pressure turret mounted lower controls including override.

Engine start/stop system with controls at platform and lower controls.

Continuous unrestricted rotation including three pass collector ring.

Five GPM (19.0 LPM) open center hydraulic system.

Chassis insulating system (lower boom insert) including fiberglass compensation link providing 12 inches (0.30 m) insulation gap.

Fiberglass inner boom and patented ELECTROGARD providing 42 in. (1.07 m) insulation gap fully retracted meeting ANSI A92.2 requirements for Category C, 46 KV and below.

Hydraulic tool power at bucket. Quick disconnect couplers not included.

ELECTROGARD and inner boom finished with white urethane paint over white gel coat.

Integral hydraulic oil reservoir with dual sight gauges and 15 gal. (56.8 l) capacity.

End mounted closed 24 in. x 30 in. x 42 in. (0.61 m x 0.76 m x 1.07 m) fiberglass platform with one step, liner and cover.

Master/slave hydraulic leveling with upper control to tilt for clean-out and rescue. Leveling control at lower controls.

Non lube bearings used at all pivot points.

Multi link hose carrier system through booms.

Boom cradle and ratchet type tie down strap.

Auto throttle control.

12 Volt DC backup pump providing power to all boom functions.

Mounting hardware for chassis/cab installation.

Full body harness and lanyard.

Painted standard white urethane.

Two operator's manuals and two service manuals.

ANSI A92.2 data plate.

SERVICE BODY

132" long x 40" high x 94" wide

24" tread plate tail shelf.

Cable access step at rear and side access.

Two (2) chrome grab handles at side access and two (2) pool type grab handles for rear tail shelf.

Stainless steel automotive rotary door latches with chain stops on all doors.

LED lighting package installed in tail shelf with additional cutouts for strobe lights.

Master door lock hook and loop system on each door with two (2) spring loaded door handles. Excludes 1st vertical curbside.

Wheel chock storage on curbside.

Grey Zolatone paint on the interior of compartments.

Street side Compartmentation:

- 1st Vertical: Two (2) adjustable shelves with dividers.
- 2nd Vertical: One (1) adjustable shelf with dividers.
- Horizontal: Open.
- Rear Vertical: Two (2) adjustable shelves with dividers.
- Hot stick shelf with rear access door.

Curbside Compartments:

- 1st Vertical: Two (2) adjustable shelves with dividers
- 2nd Vertical: Gripstrut access steps to bed area with removable composite side gate.
- Horizontal: Open.
- Rear Vertical: Five (5) fixed material hooks (1-3-1)□

CAB AND CHASSIS

- 2021 Ford F-550 4x4 cab and chassis with a CA of 84"
- GVWR: 19,500 lbs. payload plus upgrade package.
- XL Value Package includes 4.2" center-stack screen and SYNC communications system
- Power equipment package includes power windows, door locks and remote keyless entry.
- Steering wheel mounted cruise control.
- 6.7L 4V OHV Power Stroke V8 turbo diesel engine
- TorqShift 10-speed automatic transmission
- Snow plow prep package including dual alternators (Total 332-Amps)
- 4.88 limited slip axle.
- Air conditioning.
- Engine block heater
- 225/70Rx19.5G BSW traction tires.
- Radio: AM/FM stereo includes 4 speakers.
- HD vinyl 40/20/40 slit bench seat
- Trailer brake controller
- Operator Commanded Regeneration (OCR)
- Rear view camera and prep kit
- Painted Oxford White.

INSTALLATION

- Install VERSALIFT SST-40-EIH, mounting hardware, PTO and pump.
- Install rear torsion bar and ballast
- Install and paint service body and accessories.
- Install combination pintle hitch with 2" ball, D rings and 7 prong trailer connector
- Install two (2) amber strobe lights in tail shelf and two (2) strobes lights in front grill
- Install mud flaps, back up alarm and park brake interlock system.
- Furnish fire extinguisher, 3 piece triangle reflector kit and wheel chocks.
- Test ride completed unit for 1 hour.
- Test and certify per ANSI A92.