



**SKYLIFT**  
**Super 61 BackYard Mini-Arborist & Trailer**

**STANDARD EQUIPMENT**

BOOM: VERSALIFT VST6000I INSULATED TELESCOPING/ARTICULATING AERIAL DEVICE  
WORKING HEIGHT: 61'  
SIDE REACH: 40'  
PLATFORM: END-MOUNTED ROTATING 24" X 30" X 42" BUCKET  
PLATFORM CAPACITY: 300 LBS  
INSULATED CATEGORY "C" RATING PER ANSI A92.  
4-AXIS CONTROL  
TRUGUARD™ 2.0  
HYDRAULIC PLATFORM ROTATOR  
HYDRAULIC PLATFORM LEVELING  
HYDRAULIC TOOL CIRCUIT AT THE PLATFORM  
WEIGHT: 14,500 LBS  
LENGTH W/ BOOM: 24'5"  
STOWED HEIGHT: 7'7"  
WIDTH: 35" TRACKS CLOSED – 50" TRACKS OPEN  
GROUND PRESSURE: 7.7 PSI  
ENGINE: 25 HP KUBOTA DIESEL - TIER 4 COMPLIANT  
OPEN CENTER HYDRAULIC SYSTEM  
CONTROLS: FULL PRESSURE  
OUTRIGGERS: HYBRID – RADIAL TYPE  
OUTRIGGER SAFETY: OUTRIGGER INTERLOCK SYSTEM  
OUTRIGGER SPREAD: REAR 18.5' / FRONT 14' / FRONT TO BACK 20.5'

**ACCESSORIES**

EMERGENCY LOWERING  
RADIO REMOTE BELTPACK  
AUDIBLE ALARMS FOR OUTRIGGERS  
HIGH/LOW TWO SPEED THROTTLE  
ENGINE START/STOP AT BASKET  
SET OF 4 PLASTIC 18 X 18 X 1.5" OUTRIGGER PADS

**TRAILER**

25,900 LB G.V.W.R. (8' W x 25' L) WITH SOLAR BATTERY CHARGER