



We are pleased to quote the VERSALIFT VANTEL-29-NE non-insulated 28' 10" telescopic aerial platform lift 33' 10" working height including the following:

PRODUCT DESCRIPTION:

Platform capacity of 350 lbs.
Walk in hydraulic leveled 24 in. x 24 in. x 42 in. end mounted fiberglass platform with door - vinyl cover.
Heavy duty aluminum inner boom with drop down boom tip.
Drop down boom tip including manual 180° positioner.
Engine start/stop controls at platform and remote lower controls.
Non-continuous 360 degree rotation with electric limit system.
Two gpm (7.57lpm) open center hydraulic system.
Hydraulic oil reservoir with 7 gallon (26.5L) capacity built integral to pedestal.
Self locking worm gear rotation drive with shear ball bearing.
Boom articulation from 8 degrees below horizontal to 80 degrees above horizontal.
Electric rotation limit system.
Van mount pedestal and mounting hardware for low roof Transit van installation.
Hand held remote lower controls including 30 ft. cable and override.
Electric controls at platform including master control, emergency stop, and control cover.
Hydraulic power supplied by engine belt drive system.
Non-lube bearings used at all pivot points.
Multi-link plastic hose carrier system through booms.
120V wiring to platform with GFCI receptacle.
12 volt DC backup pump.
Safety harness and lanyard.
Unit painted standard white urethane.
Two operators and service manuals.
ANSI A92.2 data plate.

INSTALLATION TO INCLUDE THE FOLLOWING:

Install VERSALIFT VANTEL-29-NE, belt drive system and mounting hardware
Install and non-skid bumper extension.
Install access step with center stop light on extension.
Install SuperSprings on rear axle both sides.
Install cab partition and shelving system and roof ladder rack.
Install two (2) turret mounted amber strobes.
Install 2000 watt inverter with one Group 31 battery including battery box
Install parking brake interlock, back up alarm and bucket rest
Furnish rubber wheel chocks, fire extinguisher, first aid kit and 3 piece triangle warning kit
Test ride completed unit for 1 Hour.
Test and Certify per ANSI A92.2

VAN:

2021 Ford Transit Low Roof cargo van.

148 inch. wheel base.

3.5L PFDI V6 flex fuel gasoline engine with 10-speed automatic transmission with OD

Limited slip with 4.10 axle ratio

9,500 lbs. GVWR payload package

Vinyl dual bucket seats

235/65R 16C BSW AS tires

Dual AGM batteries (70 amp-hours each)

Front and rear vinyl floor covering

Power front windows and power remote door locks

High capacity up-fitter switches on the instrument panel

Air conditioning

AM/FM stereo radio including Bluetooth, dual USB ports and 4" multi-function display.