



Huber Series 70B
EQ# 22482

PRODUCT DESCRIPTION

Huber Series 70B

STANDARD FEATURES

Tank Capacity of 3,000 Gallons (70 barrels or 15 cubic yards)
ASME & DOT 412
Single compartment code carbon steel tank with 5/16" Shell Material
20" Top Manway w/ ladder
Anti-surge baffles inside waste tank resists surging during starting and stopping
The Tank is mounted independent of the body and is secured to the body with a 3-point mounting system
A tank lift powered by a single, 3 stage, double acting hydraulic cylinder with integrated safety valve
The tank primary shut off system with a 6" stainless steel float ball is located in the front top center of the tank with single isolation valve
The rear liquid level assembly includes a dual seal bushing with Viton o-ring seal and is replaceable from the outside of the tank
Hydraulic operated full opening rear door with integrated safety cylinder valve
4" Angled Rear Intake Valve (Air NVE, Manual Betts)
6" Rear Discharge Valve (Air NVE, Manual Betts)
Safety Prop Bars; Rear door and tank
Power to run the vacuum pump is provided by a PTO driven hydraulic system
A four way valve provides control of vacuum loading and pressure discharge
Secondary moisture trap provides added protection for the pump
Systems Controls Inside a Nema 4 waterproof electrical box
Tandem Axle Body
Open top enclosed fender/hose tray
Rear Bumper for valve protection
18" x 18" x 30" aluminum storage cabinet bolted on the passenger side
Rear Mounted Grounding Reel
Back-Up Alarm
LED Rear Work Lights
LED Side and Rear Marker Lights
Rear hose hooks (adjustable) located 2" below centerline of tank

ADDITIONAL FEATURES

Pump Package:
NVE887 MAXPAK
-532 CFM
-Fan Cooled
Electric Vibrator Ready
Roper Pump Ready

CHASSIS

2022 Peterbilt 348 Tandem Chassis, Paccar PX-9, 350HP Engine, and Allison 3000RDS-P Automatic Transmission