



## **VERSALIFT VN-555-MHI**

### **STANDARD FEATURES**

Standard platform capacity 700 lbs. (317 kg).

UNITROL single-stick mounted on curbside between boom and platform with integral safety trigger and emergency stop control. Primary TruGuard dielectric isolating system with single stick control. All control handles are isolated and tested per ANSI 92.2. The high resistive dielectric system is protected from direct environmental and job related contamination. TruGuard technology incorporates the use of full hydraulic controls with durable metal handles and linkages.

Automatic throttle control activates with trigger at single stick

Full pressure turret mounted controls with override.

Engine start/stop from platform and lower controls.

Auto throttle disable valve at platform.

Continuous rotation including 3 slip rings.

Open center hydraulic system providing 8 to 12 GPM (30-45 LPM) and 3000 psi (210 kg/cm<sup>2</sup>) system pressure.

6.5 ft. (1.98 m) jib and winch with 2000 lbs. (905 kg) capacity. Hydraulic jib articulation and extension is included. Includes 75 ft. (22.8 m) of 9/16 inch (14 mm) diameter synthetic load-line.

Lift eye on lower boom with 2500 lbs. (1125 kg) capacity.

90° hydraulic platform rotation with hydraulic tilt for cleanout or rescue.

Fiberglass upper boom tested per ANSI A92.2 for Category C 46-KV and below.

Lower boom articulation 120° with upper boom articulation 192° relative to lower boom

Vacuum flashover prevention system.

Chassis insulating system (lower boom insert) providing 18" insulation gap including accommodations to bridge insulation gap for testing per ANSI A92.2

Two (2) sets of hydraulic tool outlets at platform with 2000 psi reducing valve

Two (2) ½" diameter return lines.

External reservoir with a 30 gallon (110 L) capacity and sight level gauge.

Dual A-frame outriggers with 158 in. (4.0 m) spread with outrigger boom interlock system

Automatic boom latch. The rotary auto boom latch works off the lift hydraulic pressure to open and close.

Full length sub frame and mounting hardware for cab and chassis.

Two safety harnesses and lanyards

Two (2) operators and two (2) service manuals.

Manufactured and tested per ANSI A92.2

Continuous rotation with engine start/stop and 12 volt backup pump.

One (1) two-man 24" x 48" x 42" deep closed fiberglass basket with two steps.

Vinyl platform cover and liner for 24 in. x 48 in. x 42 in. platform.

### **LINE BODY**

156 in. x 54 in. x 94 in.

Stainless steel automotive rotary type door latches and hinges.

Chain stops on all compartment doors.

Rubber rolled crown type fenders and automotive bulb type weather stripping.

Master door lock system.

Outrigger pad storage holders with pendulum retainers.

### **STREET SIDE COMPARTMENTS**

1st vertical: 24 in. - Five (5) fixed material hooks (1-3-1).  
2nd vertical: 24 in. - Two (2) adjustable shelves with dividers  
3rd vertical: 24 in. - Two (2) adjustable shelves with dividers  
Horizontal: 60 in. - Adjustable dividers in compartment bottom  
Rear vertical: 24 in. - Two (2) adjustable shelves with dividers.  
Hot stick shelf: 156 in. long with rear dropdown access door.

### **CURBSIDE COMPARTMENTS**

1st vertical: 24 in. - Five (5) fixed material hooks (1-3-1).  
2nd vertical: 24 in. - Tread plate access steps to bed area with grab handle on each side  
3rd vertical: 24 in. - Two (2) adjustable shelves with dividers  
Horizontal: 60 in. - One (1) removable divider shelf with dividers  
Rear vertical: 24 in. - Two (2) adjustable shelves with dividers.  
Tail shelf: 30 in. tread plate tail shelf.

### **REAR LIGHTING**

Lamp light bar installed at rear of tail shelf and rubber mounted recessed rear lighting kit with LED lights.

### **WHEEL CHOCK STORAGE**

One (1) each side built into wheel wells.

### **PAINT**

Complete unit is primed and painted prior to assembly.  
Painted Winter White

### **CHASSIS**

2022 International HV507 4X4 cab and chassis  
Cummins B6.7 325 HP diesel engine @ 2400 RPM, 725 lb-ft Torque @ 1800 RPM  
Allison 3500 RDS automatic transmission  
33,000 lb. GVWR: 13,000 lb. front GAWR and 21,000 lb. rear GAWR  
22.5x8.25 powder coated steel disc wheels with 11R22.5 tires.  
124 inch C.A.  
Driver seat air suspension, passenger fixed two man bench seat  
Engine block heater 120V/1000W  
Air brake system  
Back up alarm  
Air conditioning and AM/FM radio