



Vactor Combination Sewer Cleaner EQ #: 21347 Specs

Product Description:

Vactor 2115 Combination Sewer Cleaner Model 2100 Plus

Standard Features

38" Aluminum Centrifugal Fans, Rated at 14" Negative H2O
Fluid Coupler Drive
Gear Type Step-Up Transmission to Operate Compressor
Vactor Variable Pressure Water Pump Hydraulically Driven 60 GPM at 2000 PSI
600 Foot Capacity Hose Reel with 400 Feet of 1" 2500 PSI Operating, 6250 Burst Pressure Rodder Hose
Double Acting Hydraulic Dump Hoist
Electric over Hydraulic Four-Way Power Boom Assembly with 180 Degree Rotation
Standard Pipe Package Consisting of:
 (2) 5' Aluminum Pipe Extension
 (1) 7' Catch Basin Nozzle
Full Opening Rear Door Hinged at the Top
Body Drain on Rear Door
Variable Flow Handgun Assembly with 25 Feet of 1/2" Drain Hose with Couplings Front and Rear
Sealed Electrical System
Hydraulically Tilting Hose Reel Assembly
Catch Basin Cleaning Water System Providing 20 GPM at 600 PSI through 1/2" Hose
Water Pump Overspeed Controls
Mud Flaps
239 Cubic Inch Displacement, 4-Cylinder Diesel Auxiliary Engine

DEBRIS BODY ACCESSORIES

Flat Rear Door with Hydraulic Locks and Open/Close
Debris Body Flush Out System
Stainless Steel Ball Float Shut-Off - Standard on all PD and Two Stage Units
6" Knife Valve/Rear Door with Camloc
Submersible Trash Pump- Internal Mounted - Forward Wall in Body
Centrifugal Separator (Cyclone) May Limit Water Capacity
Folding Pipe Rack/Curb Side
Folding Pipe Rack/Street Side
15 Cubic Yard Debris Body with 1300 Gallon Water and Tandem Axle Chassis
Splash Shield- Rear Door
Lube Manifold
Deflector Plate in Debris Body

WATER TANK ACCESSORIES

Low Water Alarm with Light
3" Drain Valve at Water Pump
1500 Gallon Water Capacity in lieu of 1300 Gallon

VACUUM SYSTEM ACCESSORIES

Two Stage 1.6 Deere with Fluid Coupler
8 Foot Hydraulic Telescopic Boom with 180 Degree Rotation
Wireless Boom Pendant Control

HIGH PRESSURE WATER PUMP

80 GPM/2000 PSI Water System-in lieu of Standard Water System
12 GPM Cold Weather Recirculation System– Driven from Auxiliary Engine (Fan Machines)
Accumulator System for Water System
3" Y-Strainer at Water Pump
Multi-Flow System
Front and Rear Handgun Couplers
Hydro Excavation Kit/Retractable Reel with 50' X 3/8" Hose, Handgun, and Plumbing- this System must have Option #5012-Multi Flow and Option #5010 Accumulator on the Machine (this is not Available on C-B Units)
Fan Flush Out System

HOSE REEL ACCESSORIES

800' X 1" Sewer Hose/2500 PSI (in lieu of Standard Hose)- Requires Extra Capacity Reel
Automatic Hose Level Wind Guide
Accu-Count 2.0 Digital Footage Counter and Recorder
Handgun Hose Reel- Spring Retractable Reel with 50' Hose Assembly
Telescoping Rotating Hose Reel-Capacity 500' x 1-1/4" Sewer Hose or 800' x 1" Sewer Hose
Hydraulic Shut-Off Valves at Suction, Return and Filter Line (3)
Rodder Pump Drain Valves (2)
Tow Hooks/Front
Tow Hooks/Rear
Electronic Back-Up Alarm
Increase Chassis Engine Horse Power from 300 HP to 350 HP
36 x 12 x 12 Aluminum Tool Box ****Fan
96 x 30 x 16 Aluminum Full Width Tool Box (Requires Additional 18" CA)
Engine "Regeneration Mode" Warning System
Higbee Nozzle 5'

Chassis

2011 International 7500 6 x 4 Chassis, Maxxforce 10 350 HP Engine, Allison 3000RDS Automatic Transmission

Miles: 50,868

Hours: 7,458

Aux. Engine Hours: 2,268